


SPECTROstar Omega



Microplate Reader with ultrafast UV/Vis Spectrometer



- Captures UV/Vis absorbance spectra from 220-1000 nm down to a resolution of 1 nm
- Spectrum acquisition faster than 1 second per well
- Plate formats up to 1536-well
- Fully upgradeable to FLUOstar Omega or POLARstar Omega
- Up to two integrated reagent injectors
- Plate shaking and incubation up to 60°C
- Powerful MARS Data Analysis Software



SPECTROstar Omega - Technical Specifications



Due to the modularity of BMG LABTECH's instruments, all or combinations of the features below can be installed at purchase or upgraded at any time. Please contact your local representative for more details or a quote.

Detection Modes	UV/Vis Absorbance Spectra	
Measurement Modes	Endpoint and Kinetic measurements Well Scanning	
Microplate Formats	6 to 1536-well plates, user-definable	
Light Source	High energy xenon flashlamp	
Detectors	Spectrometer with CCD	
Spectral Range	Absorbance spectrometer: 220 to 1000 nm	
Sensitivity	ABS with Spectrometer	Spectral range: 220 to 1000 nm Full spectrum captured in < 1 s/well Selectable spectral resolution: 1 - 10 nm OD range: 0 to 4 OD Accuracy: < 1% at 2 OD Precision: < 0.5% at 1 OD and < 0.8% at 2 OD Reproducibility: ±0.005 OD for 0 - 2 OD range
Read Times	Dependent on test definition	
Reagent Injection	Up to 2 built-in reagent injectors Injection at measurement position (6 to 384-well) Individual injection volumes for each well (3 to 350 µL) Variable injection speed up to 420 µL / s Up to four injection events per well Reagent back flushing	
Shaking	Linear, orbital, and double-orbital with user-definable time and speed	
Gas Vent	System to inject an atmosphere or to pull a vacuum into the reader	
Incubation	+5°C above ambient up to 45°C or 60°C	
Software	Multi-user Reader Control and MARS Data Analysis Software package included	
Dimensions	Width: 44 cm, depth: 48 cm, height: 30 cm; weight: 28 kg	
Accessories		
Stacker	Magazines for up to 50 plates - continuous loading feature	
THERMOstar	Microplate Incubator and Shaker	
Upgrades	Upgrades to include options such as additional detection modes, reagent injectors, extended temperature control, etc. are available. Please contact your local representative for more information.	

Headquarters

Germany
BMG LABTECH GmbH
Allmendgrün 8
77799 Ortenberg
Tel. +49 781 96968 -0
Fax +49 781 96968 67
germany@bmglabtech.com

Australia

BMG LABTECH Pty. Ltd.
2/24 Carbine Way
Morningside, Victoria, 3931
Tel. +61 3 5973 4744
Fax +61 3 5973 4711
australia@bmglabtech.com

France

BMG LABTECH SARL
7, Rue Roland Martin
94500 Champigny s/Marne
Tel. +33 1 48 86 20 20
Fax +33 1 48 86 47 07
france@bmglabtech.com

Japan

BMG LABTECH JAPAN Ltd.
2F TS-1 Building
1-6-2, Shimo-cho
Omiya-ku
330-0844 Saitama City
Tel. +81 48 647 7217
Fax +81 48 647 7218
japan@bmglabtech.com

UK

BMG LABTECH Ltd.
5 Merlin Centre
Gatehouse Close
Aylesbury
HP19 8DP
Tel. +44 1296 336650
Fax +44 1296 336651
uksales@bmglabtech.com

USA

BMG LABTECH Inc.
13000 Weston Parkway
Suite 109
Cary, NC 27513
Tel. +1 877 264 52 27
Fax +1 919 678 16 40
usa@bmglabtech.com